



#### GENERALITIES

The Antistatic Agent U113 cools the glue joint and prevents that the adhesive residues stick to the panel and tools. The product neutralizes the electrostatic charges that are formed during the rubbing of the cross cut saws, preventing the chips to stick to the panel or rollers.

#### CARATTERISTICS

APPEARANCE

liquid

COLOUR

light blue

#### APPLICATIONS

The Antistatic Agent U113 is sprayed immediately after the gluing of the edge, before trimming, directly on the glue joint that hardens.

Please refer to the safety data sheet before using it..

#### PACKAGE

Jerry can of 20 liter; tank 1000 liter.

#### STORAGE

It is recommended to keep the product between 10° and 30°C in original closed packaging in cool and dry places.  
Shelf life: 24 months at 20°C in original closed packages.

*The information contained in this sheet and suggestions regarding the use and application of our products correspond to the current state of our scientific and practical knowledge. However, they do not involve the assumption of any warranty and/or responsibility on the final result of the processing carried out with the use of our products due to the variability of materials and application conditions that go beyond of our control. We therefore recommend to perform preliminary tests in relation also to the subsequent machining planned for the product and the operating conditions of the finished product. This edition cancels and replaces any other precedent.*

Date: January 2023

revision n°01

THIS TECHNICAL SHEET HAS NOT TO BE CONSIDERED AS A PRODUCT SPECIFICATION -